

Product-Information

HS Crystallizer Powder

Features:	Application of HS Crystallizer Powder when treating the floor hardens the stone surface and gives it a brilliant luster. The floor is made easy-care and dirt- and slip-resistant.	
Area of application:	Suitable for all calcareous stone floors.	
Treatment:	Sprinkle (lightly) the pre-cleaned floor. Apply HS Crystallizer Powder evenly on the underground. With a cleaning device (single- or triple disk machine) and red pad, rub the product in for ca. three minutes per square meter.	
Consumption:	1 kg HS Crystallizer Powder for ca. 10 m ²	
Directions for use:	HS Crystallizer Powder has a caustic effect on all metal surfaces. Recommended are water suction devices made of plastic. Personal safety equipment is absolutely required. Future service cleaning with KH Unicide. Please absolutely heed the directions for treatment and safety in the EU safety data sheet.	
Specifications:	pH value	0.5 - 1
	Components	magnesium hexafluorosilicate oxalic acid
Canister size:	5 kg canister	
	UN number:	2853
	UBA number:	12670065
	Article number:	11019

The product information is based on laboratory studies and is a result of our experience. However, it is regarded only as non-binding directions for use. The information in no way replaces trial applications which are indispensable for use of the respective product. We are not responsible for any incorrect translation.