

Product-Information

Glass Protection GS-500

Features:	Glass Protection GS-500 protects glass from new soiling for a long time. Glass Protection forms a protective film which has a dirt-repellent effect. Dirt deposits, especially on heavily irrigated surfaces, are significantly reduced.	
	Glass Protection GS-500 does not leave streaks or corrode rubber seals when used properly.	
	The durability of the protection depends on environmental influences, weather conditions and cleaning intervals and is up to 2 years.	
Chemical behavior:	Solution of an aminofunctional silicone oil with additives in isopropanol	
Dosage:	Pure	
Treatment:	Apply very thinly to the cleaned, dry glass surface and polish immediately with a soft cloth (no microfiber).	
Consumption:	Approx. 30-35 m ² per litre, depending on weather conditions	
Directions for use:	Do not apply Glass Protection GS-500 below +10°C, in direct sunlight or on heated surfaces. Store cool and dry - keep away from sources of ignition, do not smoke. Avoid contact with skin and eyes.	
	Please absolutely heed the directions for treatment and safety in the EU safety data sheet.	
Specifications:	Product shelf life:	min. 1 year in closed canister
	pH value	5
	Components	Isopropyl alcohol, siloxanes, wetting agents
Canister size:	10 liter canister	
Article number:	10627	
UN-Number:	1219	

The product information is based on laboratory studies and is a result of our experience. However, it is regarded only as non-binding directions for use. The information in no way replaces trial applications which are indispensable for use of the respective product. We are not responsible for any incorrect translation.