

Product-Information

Metal Preservative MK-2010

GRM registered as facade protection for metal

Properties : Metal Preservative MK-2010 is used as a protective film for cleaned natural fibres anodized or black-finished eloxal, copper, brass and alloy steel.

Metal Preservative MK-2010 forms a temporary weather UV-resistant protective film. This product is polishable and leaves behind a silky brilliant film. Moreover, the layer is uniform and iridescent. It removes additionally light, superficial stains. Moreover, it is easy to remove graffiti on surfaces already treated with Metal Preservative MK-2010.

Chem. characteristics: silicone oil in solvent
contains inflammable, non toxic solvent

Dosage : pure

Directions for use: Shake very well Heidt & Schwarzfeld Metal Preservative MK-2010 before using. Distribute a thin layer of MK-2010 in a dry ground with a soft absorbent cloth. Then polish with a soft absorbent cloth while the surface is still humid.

Application: approx. 30 up to 60 g/m²

Note: Do not use Metal Preservative MK-2010 into direct sunlight or on heated plates. Do not use at a temperature below + 10°C.

Please follow carefully the instructions and safety recommendations out of the EU regulation form.

Specifications:	Expiration	minimum of 2 years
	pH-value	none
	Contents	solution of mineral oils, silicone oils and wax in mineral varnish

Container size: 10 kilo/container

UN-Number:	3295
UBA-Number:	12670047
GRM-Registration nr.	105 e
Item-Number:	10215

The product information is based upon research in labs and is the result of our experiences. Still they are only seen as unofficial. The information does not replace a pre-test in any individual case although such a pre-test is indispensable for the above use on each particular product. We are not responsible for any incorrect translation.